


euroBlade

S3/50/GW

SLATTED ACOUSTIC ABSORPTION PANEL



S3

NRC 0.65 | 105mm Overall Depth of System

PANEL DETAILS

Panel Material	Timber
Slat Depth	Sequence ranging from 17mm to 38mm
Panel Slat Width	Repetitive sequence of 17mm wide slat, 28mm wide slat, 65mm wide slat and 38mm wide slat
Slat Repetition Distance	13mm
Nominal Open Area Percentage	n/a
Panel Backing Material	Megasorber G8A

AIR GAP AND CAVITY DETAILS

Air Gap Behind Panel Material	25mm
Cavity Infill Material	25mm thick glasswool insulation

ACOUSTIC TEST REPORTING

Independent NATA Approved Test Laboratory	RMIT University (Victoria, Australia)
Date of Specimen Test	5 September 2014
Acoustic Test Report Reference Number	14-116/PD

HOW TO SPECIFY

EXAMPLE: **EB-S3/50/GW-finish-colour**

Design	Standard	S#	S3/50/GW
	Custom	C#	State custom number
Finish	Timber	T	
	Prefinished	PR	
	Polyurethane	PO	
Other	Species/colour	?	State species/colour

ACOUSTIC PERFORMANCE DATA

Frequency (Hertz)	Sound Absorption Coefficient (α_s)
100	0.05
125	0.13
160	0.22
200	0.28
250	0.44
315	0.65
400	0.94
500	0.99
630	0.90
800	0.75
1000	0.62
1250	0.54
1600	0.50
2000	0.50
2500	0.52
3150	0.51
4000	0.49
5000	0.50

