

# euroTEX SLIM with euroTEXTED

## FABRIC ABSORPTION PANEL

**NRC 0.65 | 25mm Overall depth of system**

### PANEL DETAILS

Substrate panel material	CSR Martini
Substrate panel thickness	13mm core panel
Panel face material	euroTEXTURE base cloth

### AIR GAP AND CAVITY DETAILS

Air gap behind panel material	10mm to wall
Cavity infill material	CSR Martini dECO panel

### ACOUSTIC TEST REPORTING

Independent NATA approved test laboratory	CSIRO-Melbourne
Date of specimen test	27 April 2018
Acoustic test report reference number	AC238-02

### HOW TO SPECIFY

EXAMPLE: **ET-SLIM-TEXTURE-SQUID INK**

Product	<b>euroTEX</b>	<b>ET</b>
Panel type	<b>25mm</b>	<b>SLIM</b>
	<b>45mm</b>	<b>CORE</b>
Base cloth	<b>euro</b>	<b>TEXTURE</b>
	<b>euro</b>	<b>TEXTING</b>
	<b>euro</b>	<b>TEXTED</b>
Colour Spec	<b>As per sample/range</b>	<b>?</b> <i>State species /colour</i>

### ACOUSTIC PERFORMANCE DATA

Frequency (Hertz)	Sound Absorption Coefficient ( $\alpha_s$ )
100	0.02
125	0.04
160	0.05
200	0.09
250	0.16
315	0.23
400	0.31
500	0.51
630	0.64
800	0.74
1000	0.82
1250	0.93
1600	1.00
2000	1.04
2500	1.06
3150	1.04
4000	0.99
5000	1.00

