

euroTEX SLIM with euroTEXTURE

FABRIC ABSORPTION PANEL

NRC 0.60 | 25mm Overall depth of system

PANEL DETAILS

Substrate panel material	CSR Martini
Substrate panel thickness	13mm core panel
Panel face material	euroTEXTURE base cloth

AIR GAP AND CAVITY DETAILS

Air gap behind panel material	10mm to wall
Cavity infill material	CSR Martini dECO panel

ACOUSTIC TEST REPORTING

Independent NATA approved test laboratory	CSIRO-Melbourne
Date of specimen test	27 April 2018
Acoustic test report reference number	AC238-06

HOW TO SPECIFY

EXAMPLE: **ET-SLIM-TEXTURE-SQUID INK**

Product	euroTEX	ET	
Panel type	25mm	SLIM	
	45mm	CORE	
Base cloth	euro	TEXTURE	
	euro	TEXTING	
	euro	TEXTED	
Colour Spec	As per sample/range	?	<i>State species /colour</i>

ACOUSTIC PERFORMANCE DATA

Frequency (Hertz)	Sound Absorption Coefficient (α_s)
100	0.02
125	0.02
160	0.06
200	0.09
250	0.16
315	0.20
400	0.27
500	0.42
630	0.58
800	0.67
1000	0.77
1250	0.86
1600	0.92
2000	1.02
2500	1.06
3150	1.05
4000	1.03
5000	1.02

